

## CLOPAY COMMERCIAL – MODELS 3708, 3709

# architectural series

The Clopay logo consists of a stylized 'C' icon followed by the word 'Clopay' in a bold, sans-serif font.

Model 3708, 12' x 14' Doors; Shown with 42" x 16" Lites

## POLYURETHANE INSULATED STEEL FULL-VIEW DOORS

Clopay Models 3708 (flush) and 3709 (minor ribs) are an ideal choice when visibility and/or natural light are needed. The three-layer construction with Intellicore® polyurethane insulation helps provide energy efficiency and durability.

- Intellicore® polyurethane insulation and thermal break for improved energy efficiency. R-value 12.9, U-factor 0.19.
- Three-layer construction with steel and insulation enhances durability, strength and quiet operation.
- 3-stage paint process delivers a virtually maintenance-free finish.
- Injection-molded lite frames with integral weatherseal are durable and seal against the elements. Many glass options available for visibility, privacy or energy efficiency.

[clopaycommercial.com](http://clopaycommercial.com)



Steel skins are protected through a tough, layered coating system, including a hot-dipped galvanized layer, a protective metal oxide pretreatment and a baked-on primer and top coat.

## PANEL DESIGN



## COLOR OPTIONS



\*Additional charges apply.  
Due to the printing process, colors may vary.

## CUSTOM PAINT OPTION



Color Blast® finish offers more than 1,500 Sherwin-Williams® color options to complement your building design. This durable two-part paint system has been thoroughly tested and is backed by a five-year warranty.

Due to solar reflective formulation to meet greater than a 38 LRV, some colors may not be available.

## FEATURES

### STANDARD HARDWARE

TPE astragal in corrosion-resistant retainer  
Commercial 10-ball steel rollers (nylon tires available)  
Steel step plate and lift handle  
Galvanized steel end stiles  
Inside slide lock for increased security  
2" (50.8 mm) or 3" (76.2 mm) track  
10,000 cycle springs. High cycle springs available.  
Galvanized aircraft cable with minimum 7:1 safety factor  
Variety of track configurations to meet building specifications

### MATERIALS AND CONSTRUCTION

Panel Thickness	1-3/8" (34.9 mm)
Insulation	CFC and HCFC-free Intellicore® polyurethane
R-value	12.9*
U-Factor	0.19
Air Infiltration Rate	0.12 cfm/ft <sup>2</sup>
Thermal Break	Continuous foam
Exterior Steel	27 gauge (.41 mm)
Interior Steel	27 gauge (.41 mm)
Exterior Surface	Stucco embossed, minor ribbed (3709) Stucco embossed, flush (3708)
Max Width	18'2" (5.5 m)
Max Height	16' (4.9 m)
Exterior Colors	Standard White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Gray and Trinar® White. Also available in Color Blast® finish.
Interior Color	Standard White
Limited Warranties	10-year standard paint 5-year Color Blast® finish 1-year material and workmanship

\*R-value is impacted by the number of windows and window type per section. Calculated R-values for doors featuring a full row of windows, in both insulated and non-insulated glass, is available on our website. Calculated door section R-value is in accordance with DASMA TDS-163.

For special sizes, applications and options, consult customer service at 1-800-526-4301.



For more information on these and other Clopay products, visit [clopaycommercial.com](http://clopaycommercial.com). Architects and specifiers, visit [architectdoorhelp.com](http://architectdoorhelp.com).



©2024 Clopay Corporation. All rights reserved.

## ADDITIONAL OPTIONS

### WINDOW OPTIONS



Models 3708 and 3709 are available with 1/8" clear tempered, 1/8" frosted tempered, 3/4" insulated tempered and 3/4" frosted insulated tempered glass. Additional glazing options include: matte, pebble and bronze tinted.

### HEAVY-DUTY HARDWARE (where not standard)



Double-end hinge

3" Track

High performance hardware features 10 gauge end hinges, heavy-duty top bracket and 3" sealed roller with 5/8" stem.

### MULLIONS



Carry-away, roll-away or swing-up mullions are available on select sizes.

### SAFE-T-STOP™ CHAIN HOIST



Hand chain hoist with an integral braking system provides controlled descent for sectional doors.



WindCode® design pressure (DP) up to 14 PSF depending on size. Models tested 50% greater than DP.



Increase the warranty with extreme duty hardware components.

### APPLICATION RATINGS

Car Wash/Corrosive Environments	★ ★
Fire Station/Ambulance	★ ★ ★ ★ ★
Service Station	★ ★ ★ ★ ★
Cold Storage/Condition Space	★ ★ ★ ★
Car Dealership	★ ★ ★ ★ ★
Restaurants	★ ★ ★ ★ ★
High Security	★ ★ ★ ★

### HIGH CYCLE SPRINGS



25,000, 50,000 or 100,000 cycle springs available.

### CODE COMPLIANT

This Clopay door complies with the 2015 IECC (International Energy Conservation Code) with an air infiltration rating of .40 cfm/ft<sup>2</sup> or less (IECC, Section 402.5.2), and also meets the U-Factor requirement of .37 or less (IECC, Section C402.4, for Climate Zones 1 through 8).



CMDC-3708-3709-16\_REV0424