CLOPAY COMMERCIAL - MODELS 904, 904U architectural series






ALUMINUM FULL-VIEW DOORS

Clopay's Model 904 showcases a sleek design with fewer lines and angles to its appearance. With equal stile spacing, rail and stile profiles are more proportional to each other. This design provides an aesthetically pleasing appearance making it ideal in applications such as restaurants, auto dealerships and fire stations. In addition to these features, Model 904U features Intellicore® polyurethane insulated rails and stiles.



Frame Detail





Reinforcing Fin (where applicable)



Model 904

*Model 904U R-value 3.8 with clear insulated glass.

OPTIONS

PANEL OPTIONS





Aluminum Full-View

Solid Aluminum

FRAME/SOLID PANEL COLOR OPTIONS



Standard White (Anodized) (Painted)



Bronze (Anodized)* (Anodized)*



Bronze (Painted)

Dark Bronze

(Anodized)*



Additional cost and lead time may apply. The use of "Bronze (Painted)" is recommended due to slight color variation that may occur during the anodizing process.

(Painted)







GLASS/PANEL OPTIONS



Clear Glass





Gray Tinted Glass Bronze Tinted Glass



Mirrored Glass'



Obscure Glass



Impact Rated Glass[†]



Glass*




Black Laminate Glass*



Frosted Glass







White Acrylic



Polycarbonate



Bronze Polycarbonate



Solid Aluminum Panel (Color-matched)

*Glass/acrylic panels may be combined with aluminum panels Custom glass and colors available.

†5/16" clear, white, gray and bronze laminate impact rated glass is available only on 904W8/904UW8.

PERFORMANCE OPTIONS

HEAVY-DUTY HARDWARE



Double-end Hinge



3" Track



High Performance Hardware

SPECIALTY PRODUCTS







Exhaust Port

OPTIONAL WARRANTY

Extended 8-year hardware warranty includes upgraded industrial hardware. Upgraded hardware includes 3" track and rollers, 11 gauge hinges, heavy duty brackets, solid shaft and more.



WINDCODE®



Window Style Glass

Solid Panels

Wind Load

Joint Seal

Springs

Tracks

Hardware

Warranty

Design pressures (DP) up to 52 PSF depending on configuration. Models tested 50% greater than DP.

Impact rated (W8 only)

10,000 cycle springs

3" track where applicable

Steel step plate and lift handle

*Calculated door section R-value is in accordance with DASMA TDS-163.

STANDARD SPECIFICATIONS	
Max Width	24'2" (Maximum width for Model 904U is 20'2")
Max Height	20'0"
Exterior/Interior Panel Thickness	2-1/8"
Insulation	Intellicore® polyurethane (Model 904U)
R-Value*	3.8 (Model 904U with clear insulated glass)
U-Factor	0.86 (Model 904U with clear insulated glass)
Air Infiltration Rate	0.15cfm/ft ²
End Stile Thickness	4.5" wide single up to 14'2" 6.5" wide double over 14'2"
Emboss	Recessed panel with smooth surface
Panel Style	Full-view or solid aluminum panel
Section Construction	6063-T5 extruded aluminum alloy



For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit













DSB glass, tempered glass, acrylic, thicknesses of 1/8", 1/4" and 1/2"

Insulated and non-insulated aluminum panels

2" angle mount track with standard lift

TPE astragal in corrosion-resistant retainer

Inside slide lock for increased security Standard Paint - 5 Years

Material and Workmanship – 1 Year

Galvanized aircraft cable with minimum 7:1 safety factor

Commercial 10-ball steel rollers

14 gauge hinges

Hardware - 1 Year

Color Blast® finish - 5 Years