clopay commercial-models 905, 905U, 906, 906U architectural series





ALUMINUM FULL-VIEW DOORS

Clopay Models 905 and 906 are now available with a sleek panel design offering fewer lines and angles. The proportional rail and stile profiles, along with equal spacing, provide an aesthetically pleasing appearance. This sleek door is ideal in applications such as restaurants, auto dealerships and fire stations. In addition to these features, Models 905U and 906U feature Intellicore® polyurethane insulated rails and stiles while still maintaining the sleek look.



Frame Detail



Section Joint Seal



Reinforcing Fin (where applicable) Models 905U, 906U



Models 905, 906

OPTIONS

PANEL OPTIONS AND CONFIGURATIONS






Fewer panels than traditional aluminum doors allowing for a cleaner look.

Aluminum Full-View Panel


Solid Aluminum Panel

MODELS 905 AND 905U - 7'6" TO 8'5" HIGH DOORS



20'3" to 22'2" Wide





MODELS 906 AND 906U - 7'6" TO 8'5" HIGH DOORS



Up to 10'2" Wide 10'3" to 20'2" Wide 2 Panel

3 Panel

Up to 9'0" Wide 1 Panel

2 Panel

17'3" to 22'2" Wide 3 Panel

FRAME/SOLID PANEL COLOR OPTIONS



Standard White (Painted)



(Painted)

Chocolate (Painted)



HEAVY-DUTY HARDWARE

CUSTOM PAINT OPTIONS







PERFORMANCE OPTIONS



Black (Anodized)*

Dark Bronze (Anodized)*

time may apply. The use of "Bronze (Painted)" is recommended due to slight color variation that may occur during the anodizing process.

Additional cost and lead

905/905U GLASS/PANEL OPTIONS



Hardcoated acrylic options available

White Acrylic





Solid Aluminum Panel (Color-matched)

906/906U GLASS/PANEL OPTIONS



Gray Tinted

Tempered Glass



Tempered Glass



Tempered Mirrored





Clear Laminate Glass











Gray Laminate Glass



Solid Aluminum Panel (Color-matched)

Black Laminate

Glass

Glass

Low-E glass

SPECIALTY PRODUCTS

Double-end Hinge



Exhaust Port

Glass

Wind Load

Joint Seal

Springs

Tracks

Hardware

Warranty

3" Track

WINDCODE®

Design pressures (DP) up to 18 PSF depending on configuration. Models tested 50% greater than DP.



STANDARD SPECIFICATIONS

Max Width	22'2" (905, 906) 20'2" (905U, 906U)
Max Height	16'0"
Exterior/Interior Panel Thickness	2-1/8"
Insulation	Intellicore® polyurethane (Models 905U and 906U)
End Stile Thickness	4.5" wide single up to 14'2" 6.5" wide double over 14'2"
Emboss	Recessed panel with smooth surface
Panel Style	Full-view or solid aluminum panel
Section Construction	6063-T5 extruded aluminum alloy
Solid Panels	Insulated and non-insulated aluminum panels
Window Style	Full-view



For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit architectdoorhelp.com.









905/905U - Acrylic

Non-impact rated

10,000 cycle springs

3" track where applicable

Steel step plate and lift handle

Acrylic thickness of 1/8" Laminate glass thickness of 1/4"

906/906U – Tempered and laminate glass Tempered glass thicknesses of 1/8", 1/4" and 1/2"

2" angle mount track with standard lift

TPE astragal in corrosion-resistant retainer

Inside slide lock for increased security Standard Paint - 5 Years

Material and Workmanship - 1 Year

Galvanized aircraft cable with minimum 7:1 safety factor



Commercial 10-ball steel rollers

11 gauge hinges

Hardware - 1 Year

Color Blast® finish - 5 Years