

STEEL ROLL-UP MODELS

200M | MINI-STORAGE DOOR

- Yard Barns
- Mini-Warehouses
- Storage Sheds
- Boat Houses
- Other Light-Duty Applications
- Available in sizes 2'6" wide × 3' high through 12' wide × 14' high


400M | HEAVY-DUTY DOOR

- Trucking Terminals
- Post Frame Buildings
- Light Industrial Warehousing
- Job Site Trailers
- Farm Machinery Storage Sheds
- Available in sizes 2'6" wide × 3' high through 18' wide × 18' high

HOW TO MEASURE

Roll-up doors are ordered to the size of the rough opening.


Note that the door will be *larger* than the rough opening because it installs *behind* the opening. Reference the sideroom and headroom requirements in the charts below for the overlap amounts.



Measure Your Rough Opening


$$\frac{\text{width}}{\text{height}}$$

The rough opening dimension is the size you need to order.



Determine Bracket Mounting Surface Areas

Refer to the height charts below for minimum areas required for your door to operate correctly.



Determine Clearance Areas

Refer to the height charts below for minimum areas required for your door to operate correctly.

200M	DOOR HEIGHT			
	Up to 7'4"	7'5"– 8'8"	8'9"– 10'	10'1"– 14'
C = Header Bracket Width	4"	4"	4"	4"
D = Header Bracket Height	7½"	7½"	7½"	7½"
E = Sideroom	4"	4"	4"	4"
F = Backroom	17"	17½"	18½"	19¼"
G = Headroom	15½"	16"	17"	18"

400M	DOOR HEIGHT				
	Up to 8'	8'1"– 10'	10'1"– 14'	14'1"– 16'	16'1"– 18'
C = Header Bracket Width	8½"	8½"	8½"	8½"	8½"
D = Header Bracket Height	9"	9"	9"	9"	9"
E = Sideroom	6"	6"	6"	6"	6"
F = Backroom	20"	21"	21"	21"	22"
G = Headroom	20"	21"	22"	22"	22"



GARAGE DOORS

STEEL ROLL-UP DOORS






EZ-SET® Roll-Up Spring System

Allows a simple method of tensioning while more accurately fine tuning the springs. You just click it (includes winding bar tool).



Radial Ball Bearings

These permanently lubricated bearings require no maintenance.



Steel Barrel Tube Housing

The tube housing protects the springs and strengthens the axle, producing smoother operation and improved durability.



26 Gauge Steel Curtain

This premium steel yields greater door strength and minimizes curtain damage.



Heavy Gauge Steel Latch

Featuring a cover plate made from heavy gauge steel that protects against tampering.



Minimal Backroom Required

No horizontal track. Door rolls up above doorway.

FEATURE AVAILABILITY

	200M	400M
EZ-SET® Roll-Up Spring System	Winding	Ratchet
Radial Ball Bearings	■	■
Siliconized Polyester Paint System	■	■
Enclosed Barrel Assembly	■	■
Mini Lock Latch	■	
Double Inside Slide Lock		■
Nylon Strapping on Edges of Curtain		■
Motor Operated Option		■
Reduced Drive Chain Hoist*		■

**Optional on doors up to 10' wide x 10' high.
Standard on doors over 10' wide x 10' high.*


Operator Recommendations (Model 400M Only)

Model MJ medium-duty jackshaft operator is available and sold separately as an option when ordering.


ULTRA DURABLE POLYESTER PAINT COLORS



LIMITED PAINT
WARRANTY



Glossy White




Satin White




Silhouette Gray



Light Stone



Continental Brown



Dark Bronze



Cedar Red



Forest Green

Due to limitations in the printing process, colors shown may vary from actual product.